

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Capadur LasurGel Teak

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Solvent-borne coatings

Recommended restrictions : within adequate application - none
on use

1.3 Details of the supplier of the safety data sheet

Company : Caparol Farben Lacke GmbH
Roßdörfer Straße 50
64372 Ober-Ramstadt

Telephone : +496154710
Telefax : +4961547170222

Website :
E-mail address Responsible/issuing person : msds@dr-rmi.com

1.4 Emergency telephone

Emergency telephone 1 : +49613284463 GBK GmbH

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapor.

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.

Response:

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Additional Labeling

EUH208 Contains propiconazole (ISO), 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

Version 2.2 Revision Date: 06.09.2023 SDS Number: 6007524 Date of last issue: 16.02.2022
Date of first issue: 26.07.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Alkyd-resin-based wood varnish, solvent-containing, with film protection

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | Concentration (% w/w) |
|---|---|---|--------------------------|
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha | 64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33, 01-2119486659-16 | Asp. Tox. 1; H304 EUH066 | $\geq 50 - < 70$ |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha | 64742-48-9 265-150-3 649-327-00-6 01-2119457273-39, 01-2119463258-33 | Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 EUH066 | $\geq 10 - < 20$ |
| Amines, coco alkyl, ethoxylated, compds. with polyethylene glycol monooleyl ether phosphate | 120968-16-3 | Skin Irrit. 2; H315 Eye Irrit. 2; H319 | $\geq 1 - < 10$ |
| propiconazole (ISO) | 60207-90-1 262-104-4 613-205-00-0 | Acute Tox. 4; H302 Skin Sens. 1; H317 Repr. 1B; H360D Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 | $\geq 0,25 - < 0,3$ |
| 3-iodo-2-propynyl butylcarbamate | 55406-53-6 259-627-5 616-212-00-7 01-2120762115-60 | Acute Tox. 4; H302 Acute Tox. 3; H331 Eye Dam. 1; H318 Skin Sens. 1; H317 STOT RE 1; H372 (larynx) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 | $\geq 0,1 - < 0,25$ |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|----------------|------------------------------|------------------------|---|
| Version 2.2 | Revision Date: 06.09.2023 | SDS Number: 6007524 | Date of last issue: 16.02.2022 Date of first issue: 26.07.2019 |
|----------------|------------------------------|------------------------|---|

| | | | |
|--|--|---|--|
| | | M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1 | |
|--|--|---|--|

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : Never give anything by mouth to an unconscious person.
If you feel unwell, seek medical advice (show the label where possible).
Move out of dangerous area.
First aider needs to protect himself.
- If inhaled : Call a physician.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
Move to fresh air.
- In case of skin contact : Do NOT use solvents or thinners.
In case of contact, immediately flush skin with soap and plenty of water.
Take off all contaminated clothing immediately.
- In case of eye contact : If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
- If swallowed : Seek medical advice.
Clean mouth with water and drink afterwards plenty of water.
If swallowed, DO NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Do not use a solid water stream as it may scatter and spread fire.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.
In case of fire hazardous decomposition products may be produced such as:
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.
In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Do not get in eyes, on skin, or on clothing.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
Ensure adequate ventilation.
Remove all sources of ignition.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
Do not flush into surface water or sanitary sewer system.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Keep in suitable, closed containers for disposal.
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

6.4 Reference to other sections

For further information see Section 7 of the safety data sheet.
, For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Non-sparking tools should be used.
For personal protection see section 8.
Avoid exceeding the given occupational exposure limits (see section 8).
Provide sufficient air exchange and/or exhaust in work rooms.

No interior use.

In addition, the current technical information for this product and its application on www.caparol.com must be observed.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hygiene measures : Avoid contact with the skin and the eyes. Wash hands before eating, drinking, or smoking. Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Store between 41 and 77 °F in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

Version 2.2 Revision Date: 06.09.2023 SDS Number: 6007524 Date of last issue: 16.02.2022
Date of first issue: 26.07.2019

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---|--|-------------------------------|--------------------------------------|-------------|
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha | 64742-48-9 | AGW | 300 mg/m ³ | DE TRGS 900 |
| | Peak-limit category: 2;(II) | | | |
| | Further information: Group exposure limit for hydrocarbon solvent mixtures | | | |
| Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha | 64742-48-9 | AGW | 300 mg/m ³ | DE TRGS 900 |
| | Peak-limit category: 2;(II) | | | |
| | Further information: Group exposure limit for hydrocarbon solvent mixtures | | | |
| 3-iodo-2-propynyl butylcarbamate | 55406-53-6 | AGW (Vapour and aerosols) | 0,005 ppm 0,058 mg/m ³ | DE TRGS 900 |
| | Peak-limit category: 2;(I) | | | |
| | Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child, Substance sensitizing through the skin | | | |

8.2 Exposure controls

Personal protective equipment

Eye/face protection : DGUV Regulation 112-192 - Use of eye and face protection

Goggles

Hand protection

Material : Nitrile rubber
Glove thickness : 0,2 mm
Protective index : Class 3

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Before removing gloves clean them with soap and water. Wear suitable gloves tested to EN374.
DGUV Regulation 112-195 - Use of protective gloves

Skin and body protection : Safety shoes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

Long sleeved clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Skin should be washed after contact.

During spray application: impervious clothing

Respiratory protection : Roller application or brushing: This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

DGUV Regulation 112-190 - Use of breathing equipment

During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | | |
|--|---|----------------|
| Physical state | : | liquid |
| Color | : | brown |
| Odor | : | characteristic |
| Odor Threshold | : | Not relevant |
| Melting point/freezing point | : | not determined |
| Boiling point/boiling range | : | not determined |
| Upper explosion limit / Upper flammability limit | : | not determined |
| Lower explosion limit / Lower flammability limit | : | not determined |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

| | | |
|--|---|---|
| Flash point | : | 55 °C Method: ISO 1523 |
| Autoignition temperature | : | not determined |
| Decomposition temperature | : | Not applicable |
| pH | : | substance/mixture is non-soluble (in water) |
| Viscosity | | |
| Viscosity, dynamic | : | > 100 mPa.s (40 °C) Method: ISO 3219 |
| Viscosity, kinematic | : | >= 21 mm ² /s (40 °C) |
| Flow time | : | Not applicable |
| Solubility(ies) | | |
| Water solubility | : | partly miscible |
| Partition coefficient: n-octanol/water | : | not determined |
| Vapor pressure | : | not determined |
| Relative density | : | not determined |
| Density | : | 0,83 g/cm ³ (20 °C) Method: DIN EN ISO 2811-1 |
| Bulk density | : | Not applicable |
| Relative vapor density | : | Heavier than air. |

9.2 Other information

| | | |
|------------|---|----------------|
| Explosives | : | Not applicable |
|------------|---|----------------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

Oxidizing properties : Not applicable

Flammability (liquids) : Sustains combustion

Evaporation rate : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.
Hazardous decomposition products formed under fire conditions.

10.4 Conditions to avoid

Conditions to avoid : Protect from frost, heat and sunlight.

10.5 Incompatible materials

Materials to avoid : Incompatible with acids and bases.
Incompatible with oxidizing agents.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

Components:

propiconazole (ISO):

Acute oral toxicity : LD50 (Rat, male and female): 1.517 mg/kg

Acute dermal toxicity : LD50 (Rat): > 4.000 mg/kg

3-iodo-2-propynyl butylcarbamate:

Acute oral toxicity : LD50 (Rat): 500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0,763 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

propiconazole (ISO):

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:

Partition coefficient: n-octanol/water : log Pow: 1,99 - 18,02 (20 °C)
pH: 7

Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha:

Partition coefficient: n-octanol/water : log Pow: 1,99 - 18,02 (20 °C)
pH: 7

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

3-iodo-2-propynyl butylcarbamate:

Partition coefficient: n-
octanol/water : log Pow: 2,81 (25 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : .
Waste should not be disposed of via wastewater.

Contaminated packaging : Only completely emptied containers should be given for recycling.

Waste Code : used product
080112, waste paint and varnish other than those mentioned
in 08 01 11*

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

SECTION 14: Transport information

14.1 UN number or ID number

| | | |
|------|---|---------|
| ADN | : | UN 1263 |
| ADR | : | UN 1263 |
| RID | : | UN 1263 |
| IMDG | : | UN 1263 |
| IATA | : | UN 1263 |

14.2 UN proper shipping name

| | | |
|------|---|-------|
| ADN | : | PAINT |
| ADR | : | PAINT |
| RID | : | PAINT |
| IMDG | : | PAINT |
| IATA | : | Paint |

14.3 Transport hazard class(es)

| | Class | Subsidiary risks |
|------|-------|------------------|
| ADN | : 3 | |
| ADR | : 3 | |
| RID | : 3 | |
| IMDG | : 3 | |
| IATA | : 3 | |

14.4 Packing group

| | |
|------------------------------|---------|
| ADN | |
| Packing group | : III |
| Classification Code | : F1 |
| Hazard Identification Number | : 30 |
| Labels | : 3 |
| ADR | |
| Packing group | : III |
| Classification Code | : F1 |
| Hazard Identification Number | : 30 |
| Labels | : 3 |
| Tunnel restriction code | : (D/E) |
| RID | |
| Packing group | : III |
| Classification Code | : F1 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

- REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59) : This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be generated.
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
- Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable
- REACH - List of substances subject to authorisation (Annex XIV) : None
- Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS
- 34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)
- Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)
- Product code for laquers and paints / Giscode : M-KH02F Solvent-based varnishes / wood glaze, aromatics removed, active agents
- . : BSL40 Coating materials, strongly solvent-based, aromatic-free, classified
- Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 75,01 %

Volatile organic compounds : Directive 2004/42/EC
< 76 %
< 630 g/l

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

15.2 Chemical Safety Assessment

A Chemical Safety Assessment is not required for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.
H302 : Harmful if swallowed.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H319 : Causes serious eye irritation.
H331 : Toxic if inhaled.
H336 : May cause drowsiness or dizziness.
H360D : May damage the unborn child.
H372 : Causes damage to organs through prolonged or repeated exposure if inhaled.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Repr. : Reproductive toxicity
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitization
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information:

No exposure scenario communication is required for this product according to REACH Regulation No. 1907/2006 EC.

Communication of Uses is not required in accordance with REACH Article 31(1)(a) - registered substances / mixtures do not meet the criteria for classification as hazardous in accordance with Regulations 1272/2008 EC or 1999/45/EC.

Sources of key data used to compile the Material Safety Data Sheet:

ECHA WebSite

ACGIH (American Conference of Government Industrial Hygienists). 2014 TLVs and BEIs.

Threshold Limit Values (TLVs) for chemical substances and physical agents and Biological Exposure Indices (BEIs) with Seventh Edition documentation. 2014 ACGIH, Cincinnati OH

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

GESTIS - Database on hazardous substances - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA, Institute for Occupational Safety and Health of the German Social Accident Insurance)

Toxnet - Toxicology Data Network

Classification of the mixture:

| | |
|-------------------|------|
| Flam. Liq. 3 | H226 |
| Aquatic Chronic 3 | H412 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended
by Commission Regulation (EU) 2020/878



DE / EN

Capadur LasurGel Teak

| | | | |
|---------|----------------|-------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 16.02.2022 |
| 2.2 | 06.09.2023 | 6007524 | Date of first issue: 26.07.2019 |

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our up-stream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly.

DE / EN